

**Amendments to the Claims:**

Claims 9-17 and 19-26 were pending in this application. Please cancel claims 9-15 and 26, and amend claims 24 and 25 follows:

1                   1.-15. (canceled)

1                   16. (previously presented) A method of reporting utilization of call  
2 queues, each call placed from a caller to a subscriber line, the call processed by an  
3 Advanced Intelligent Network (AIN) having at least one central office switch and a  
4 service control point (SCP) in electrical communication with a plurality of subscriber  
5 switches via a signaling network, the method comprising:  
6                   providing an intelligent peripheral in electrical communication with the  
7 at least one central office switch and the SCP, the intelligent peripheral equipped with  
8 call queuing functionality;  
9                   receiving each of a plurality of calls to access the subscriber line;  
10                  monitoring call signaling to detect a termination attempt trigger;  
11                  launching a query at the SCP for receipt by the intelligent peripheral  
12 requesting the queue status of the subscriber line in response to the detected  
13 termination attempt trigger;  
14                  forwarding the call to the intelligent peripheral to be added to the  
15 queue in response to a determination that the queue is active;  
16                  delivering the call to the subscriber and setting a next event list trigger  
17 to determine the status of a subscriber line in response to a determination that the  
18 queue is empty;  
19                  connecting the call to the subscriber line in response to a determination  
20 that the line is idle;  
21                  forwarding the call to the intelligent peripheral to be placed in queue  
22 in response to a determination that the subscriber line is busy;  
23                  collecting queue utilization information about each queued call in the  
24 service control point; and

25                   generating queue utilization statistics based on the collected queue  
26   utilization information.

1                   17. (original) A method of reporting utilization of call queues in  
2   claim 16, the method further comprising:  
3                   monitoring the subscriber line to notify the SCP when the line is idle;  
4                   placing a call from the intelligent peripheral to the subscriber in  
5   response to a determination that the subscriber line is idle;  
6                   forwarding answer supervision to the intelligent peripheral in response  
7   to the call from the intelligent peripheral being answered by the subscriber; and  
8                   transferring and connecting the subscriber and the caller at the central  
9   office switch.

1                   18. (canceled).

1                   19. (original) A method of reporting utilization of call queues in  
2   claim 16 wherein generating queue utilization statistics is performed by a data server  
3   in communication with the service control point.

1                   20. (original) A method of reporting utilization of call queues in  
2   claim 19 wherein the data server aggregates information for each of a plurality of  
3   subscribers.

1                   21. (original) A method of reporting utilization of call queues in  
2   claim 16, the method further comprising formatting the queue utilization statistics for  
3   access by a subscriber over the Internet.

1                   22. (original) A method of reporting utilization of call queues in  
2   claim 16, the method further comprising sending queue utilization statistics to the  
3   subscriber.

1                   23. (original) A method of reporting utilization of call queues in  
2 claim 16, the method further comprising:  
3                   aggregating subscriber data across a plurality of report periods; and  
4                   calculating utilization information based on the aggregated data.

1                   24. (currently amended) For use in an Advanced Intelligent Network  
2 (AIN) equipped with termination attempt trigger (TAT) capability, the AIN having  
3 at least one central office switch and a service control point (SCP) in electrical  
4 communication with a plurality of subscriber switches via a signaling network, a  
5 method of reporting utilization of queuing of a plurality of telephone calls from a  
6 caller to a subscriber telephone line comprising:  
7                   providing an intelligent peripheral in electrical communication with the  
8 central office switch and the SCP, the intelligent peripheral equipped with queuing  
9 functionality for each of the subscribers;  
10                  monitoring signaling to detect a TAT;  
11                  generating a first electrical signal for receipt by the SCP in response  
12 to the detected TAT;  
13                  generating a second electrical signal at the SCP for receipt by the  
14 intelligent peripheral requesting status of a queue associated with the subscriber line;  
15                  generating a third electrical signal at the SCP for receipt by the  
16 subscriber switch instructing the subscriber switch to forward the call to the  
17 intelligent peripheral to be added to the queue in response to a determination that the  
18 queue is active;  
19                  determining queue utilization information at the SCP about each  
20 queued call; and  
21                  generating queue utilization statistics based on the queue utilization  
22 information  
23                  generating a fourth electrical signal at the subscriber switch for receipt  
24 by the SCP in response to a determination that the subscriber line is busy;

25                    generating a fifth electrical signal at the SCP for receipt by the  
26   subscriber switch instructing the subscriber switch to forward the call to the  
27   intelligent peripheral to be placed in the queue;  
28                    generating a sixth electrical signal at the SCP for receipt by the  
29   subscriber switch instructing the subscriber switch to set a monitor on the subscriber  
30   line and to notify the SCP when the line is idle;  
31                    generating a seventh electrical signal at the subscriber switch for  
32   receipt by the SCP in response to a determination that the subscriber line is idle;  
33                    generating an eighth electrical signal at the SCP for receipt by the  
34   intelligent peripheral instructing the intelligent peripheral to call the subscriber via  
35   the central office switch;  
36                    generating a ninth electrical signal at the central office switch for  
37   receipt by the intelligent peripheral to forward answer supervision to the intelligent  
38   peripheral in response to the call being answered by the subscriber; and  
39                    generating a tenth electrical signal at the intelligent peripheral for  
40   receipt by the central office switch to transfer and connect the subscriber and the  
41   caller at the central office switch.

1                    25. (currently amended) The method of claim 24 wherein the AIN  
2   is further equipped with Next Event List (NEL) functionality, the method further  
3   comprising:

4                    generating an eleventh ~~a fourth~~ electrical signal at the SCP for receipt  
5   by the subscriber switch instructing the subscriber switch to deliver the call to the  
6   subscriber and to set a NEL to determine the status of the subscriber line in response  
7   to a determination that the queue is empty; and

8                    connecting the call to the subscriber line in response to a determination  
9   that the subscriber line is idle.

1                    26. (canceled).